

Technical Data Sheet

SL-D/E

Double-tube 4-Pin

Plug-in Compact Fluorescent Lamps



Technical/Electrical Data & Physical Characteristics

Item Number	Description	Wattage	Bulb	Life	Base	CRI	Light Output	Colour Temperature	Bulb Diameter	M.O.L.	Case Qty.
G13000-003	SL13D/E/827/4P	13W	2xT4	10,000 hrs	G24q-1	82	900 lm	2700K	27mm	130mm	50
G13020-003	SL13D/E/830/4P	13W	2xT4	10,000 hrs	G24q-1	82	900 lm	3000K	27mm	130mm	50
G13040-003	SL13D/E/835/4P	13W	2xT4	10,000 hrs	G24q-1	82	900 lm	3500K	27mm	130mm	50
G13060-003	SL13D/E/841/4P	13W	2xT4	10,000 hrs	G24q-1	82	900 lm	4100K	27mm	130mm	50
G13080-003	SL13D/E/865/4P	13W	2xT4	10,000 hrs	G24q-1	82	900 lm	6500K	27mm	130mm	50
G13100-003	SL18D/E/827/4P	18W	2xT4	10,000 hrs	G24q-2	82	1,200 lm	2700K	27mm	145mm	50
G13120-003	SL18D/E/830/4P	18W	2xT4	10,000 hrs	G24q-2	82	1,200 lm	3000K	27mm	145mm	50
G13140-003	SL18D/E/835/4P	18W	2xT4	10,000 hrs	G24q-2	82	1,200 lm	3500K	27mm	145mm	50
G13160-003	SL18D/E/841/4P	18W	2xT4	10,000 hrs	G24q-2	82	1,200 lm	4100K	27mm	145mm	50
G13200-003	SL26D/E/827/4P	26W	2xT4	10,000 hrs	G24q-3	82	1,800 lm	2700K	27mm	165mm	50
G13220-003	SL26D/E/830/4P	26W	2xT4	10,000 hrs	G24q-3	82	1,800 lm	3000K	27mm	165mm	50
G13240-003	SL26D/E/835/4P	26W	2xT4	10,000 hrs	G24q-3	82	1,800 lm	3500K	27mm	165mm	50
G13260-003	SL26D/E/841/4P	26W	2xT4	10,000 hrs	G24q-3	82	1,800 lm	4100K	27mm	165mm	50
G13280-003	SL26D/E/865/4P	26W	2xT4	10,000 hrs	G24q-3	82	1,800 lm	6500K	27mm	165mm	50

Certifications



TCLP
COMPLIANT



EOL PROTECTED

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.

www.symbanlighting.com

Symban Lighting Corp.
99 First Gulf Blvd. Brampton, ON
T. 905.450.5999 | F. 905.450.6665