

Technical Data Sheet

SL-Q & SL-P

High Wattage Screw-in Compact Fluorescent Lamps



Technical/Electrical Data & Physical Characteristics

| Item Number | Description | Wattage | Voltage | Life | Base | Tube Configuration | CRI | Light Output | Colour Temperature | Diameter | M.O.L. | Case Qty. |
|-------------|---------------------|---------|---------|-----------|------|--------------------|-----|--------------|--------------------|----------|--------|-----------|
| G50850-003 | SL65Q/841/MED 120V | 65W | 120V | 8,000 hrs | E26 | 4 x T5 | 82 | 3,900 lm | 4100K | 73mm | 274mm | 10 |
| G50855-003 | SL65Q/850/MED 120V | 65W | 120V | 8,000 hrs | E26 | 4 x T5 | 82 | 3,900 lm | 5000K | 73mm | 274mm | 10 |
| G50870-003 | SL85Q/841/MED 120V | 85W | 120V | 8,000 hrs | E26 | 4 x T5 | 82 | 5,000 lm | 4100K | 88mm | 345mm | 10 |
| G50875-003 | SL85Q/850/MED 120V | 85W | 120V | 8,000 hrs | E26 | 4 x T5 | 82 | 5,000 lm | 5000K | 88mm | 345mm | 10 |
| G50890-003 | SL105P/841/MED 120V | 105W | 120V | 8,000 hrs | E26 | 5 x T5 | 82 | 6,150 lm | 4100K | 88mm | 309mm | 10 |
| G50895-003 | SL105P/850/MED 120V | 105W | 120V | 8,000 hrs | E26 | 5 x T5 | 82 | 6,150 lm | 5000K | 88mm | 309mm | 10 |
| G50910-003 | SL125P/841/MED 120V | 125W | 120V | 8,000 hrs | E26 | 5 x T5 | 82 | 7,400 lm | 4100K | 88mm | 354mm | 10 |
| G50915-003 | SL125P/850/MED 120V | 125W | 120V | 8,000 hrs | E26 | 5 x T5 | 82 | 7,400 lm | 5000K | 88mm | 354mm | 10 |



Symban Lighting Corp.
99 First Gulf Blvd. Brampton, ON
T. 905.450.5999 | F. 905.450.6665

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.

www.symbanlighting.com