

# Technical Data Sheet

## ORBIT® -DIMMABLE

### Screw-in Dimmable & Dimmable Cold Cathode Spiral Compact Fluorescent Lamps



#### Technical/Electrical Data

Item Number	Description	Wattage	Voltage	Life	Base	CRI	Light Output	Colour Temperature	Dimmable Range	Min. Start Temp.
<b>SPIRAL</b>										
G51180-003	SL13/O/ES/DIM/827 120V	13W	120V	8,000 hrs	E26	82	900 lm	2700K	10%-100%	-20°C
G51390-003	SL20/O/ES/DIM/827 120V	20W	120V	8,000 hrs	E26	82	1450 lm	2700K	10%-100%	-20°C
G51480-003	SL23/O/ES/DIM/827 120V	23W	120V	8,000 hrs	E26	82	1550 lm	2700K	10%-100%	-20°C
<b>COLD CATHODE</b>										
G65220-003	SL8/O/A19/ES/CL/DIM/CC/827 120V	8W	120V	25,000 hrs	E26	82	320 lm	2700K	5%-100%	-20°C
G65230-003	SL8/O/A19/ES/IF/DIM/CC/827 120V	8W	120V	25,000 hrs	E26	82	320 lm	2700K	5%-100%	-20°C

#### Physical Characteristics

Item Number	Description	Finish	Diameter	M.O.L.	Case Qty.	Energy Star
<b>SPIRAL</b>						
G51180-003	SL13/O/ES/DIM/827 120V	n/a	56mm	124mm	10	
G51390-003	SL20/O/ES/DIM/827 120V	n/a	60mm	130mm	10	
G51480-003	SL23/O/ES/DIM/827 120V	n/a	60mm	137mm	10	
<b>COLD CATHODE</b>						
G65220-003	SL8/O/A19/ES/CL/DIM/CC/827 120V	clear	60mm	122mm	25/50	
G65230-003	SL8/O/A19/ES/IF/DIM/CC/827 120V	frosted	60mm	122mm	25/50	



**Symban Lighting Corp.**  
 99 First Gulf Blvd. Brampton, ON  
 T. 905.450.5999 | F. 905.450.6665

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.