

Technical Data Sheet

SY-1000-MH-TRI-KIT

R11300-003

Magnetic High Intensity Discharge Ballast
 High Power Factor - Constant Wattage Autotransformer
 Class H (180°C) insulation system
 Type 1 Outdoor | Class P
 No PCB'S




Technical/Electrical Data

No. of Lamps	Lamps Operated	Rated Lamp Wattage	Input Operating Wattage	Input Voltage	Frequency	Power Factor	Line Regulation	Lamp Voltage	Open Circuit Voltage
1	1000W MH 1000W MV	1000W	1060W	120/277/347V	60Hz	≥0.90	+/- 10%	250V	350V ~ 524V

Starting Current	Operating Current	Lamp Current	Lamp Efficiency	ANSI Lamp Code	Ignitor Model No.	Min. Starting Temperature	Max. Operating Temperature	Max. Distance to Lamp
7.80/3.20/2.50A	9.30/3.90/3.20A	4.30A	0.83	M47, H36	n/a	-30°C	155°C	2ft.


Physical Characteristics

Length (L)	Width (W)	Core Height (H)	Ballast Height (B)	Mounting Length (ML1)	Mounting Length (ML2)	Mounting Width (MW)	Mounting Hole Diameter	Ballast Weight
152.4mm	108.2mm	88mm	145mm	136.5mm	111mm	98.4mm	6.5mm	10.50 kg



Electrical Wiring Diagram

GROUND BALLAST CORE AND METALLIC CAPACITOR CASE
 INSTALL IN ACCORDANCE WITH NATIONAL AND LOCAL ELECTRICAL CODES



Product Labels

Symban
 120/277/347V
 9.30A/4.00A/3.00A
 HIGH POWER FACTOR
 SY-1000-MH-TRI

H09

LAMP TYPES
 1000W MH M47
 1000W MV H36

24mfd 480V capacitor
 Class HClass H (180°C) insulation system
 OCV: 300V
 Constant Wattage Autotransformer

GROUND BALLAST CORE AND METALLIC CAPACITOR CASE
 INSTALL IN ACCORDANCE WITH NATIONAL AND LOCAL ELECTRICAL CODES



Symban Lighting Corp.
 99 First Gulf Blvd. Brampton, ON
 T. 905.450.5999 | F. 905.450.6665

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.

www.symbanlighting.com