

Technical Data Sheet

HIGH PRESSURE SODIUM

General Service High Pressure Sodium Lamps



Technical/Electrical Data

Item Number	Description	Wattage	Colour Temperature	CRI	Life	Light Output	ANSI	Operating Position
L10000-003	LU35/MED/ECO	35W	2000K	20	16000 hrs	2200 lm	S76	universal
L11000-003	LU50/MED/ECO	50W	2000K	20	24000 hrs	3800 lm	S68	universal
L12000-003	LU70/MED/ECO	70W	2000K	20	24000 hrs	6000 lm	S62	universal
L12100-003	LU70/ECO	70W	2000K	20	24000 hrs	6000 lm	S62	universal
L13000-003	LU100/MED/ECO	100W	2000K	20	24000 hrs	9000 lm	S54	universal
L13100-003	LU100/ECO	100W	2000K	20	24000 hrs	9000 lm	S54	universal
L14000-003	LU150/MED/ECO	150W	2000K	20	24000 hrs	15000 lm	S55	universal
L14100-003	LU150/ECO	150W	2000K	20	24000 hrs	15000 lm	S55	universal
L15000-003	LU200/ECO	200W	2000K	20	24000 hrs	22000 lm	S66	universal
L16000-003	LU250/ECO	250W	2000K	20	24000 hrs	28000 lm	S50	universal
L17000-003	LU400/ECO	400W	2000K	20	24000 hrs	48000 lm	S51	universal
L21000-003	LU1000/ECO	1000W	2000K	20	24000 hrs	130000 lm	S52	universal

Physical Characteristics

Item Number	Description	Lamp	Base	Finish	Diameter	M.O.L.	Case Qty.
L10000-003	LU35/MED/ECO	ED17	E26	clear	55mm	138mm	12
L11000-003	LU50/MED/ECO	ED17	E26	clear	55mm	138mm	12
L12000-003	LU70/MED/ECO	ED17	E26	clear	55mm	138mm	12
L12100-003	LU70/ECO	ED23.5	E39	clear	76mm	197mm	12
L13000-003	LU100/MED/ECO	ED17	E26	clear	55mm	138mm	12
L13100-003	LU100/ECO	ED23.5	E39	clear	76mm	197mm	12
L14000-003	LU150/MED/ECO	ED17	E26	clear	55mm	138mm	12
L14100-003	LU150/ECO	ED23.5	E39	clear	76mm	197mm	12
L15000-003	LU200/ECO	ED18	E39	clear	58mm	248mm	12
L16000-003	LU250/ECO	ED18	E39	clear	58mm	248mm	12
L17000-003	LU400/ECO	ED18	E39	clear	58mm	248mm	12
L21000-003	LU1000/ECO	E25	E39	clear	80mm	383mm	12



Symban Lighting Corp.
 99 First Gulf Blvd. Brampton, ON
 T. 905.450.5999 | F. 905.450.6665

All specifications are subject to change without notice. Actual performance may vary depending on operating conditions.